


Converter Box Series Hardware Specification	
Model	HD2HD-S
Product Photo	
Description	HDMI to HDMI Up/Down Converter
Feature	<ul style="list-style-type: none"> ● Built-in up/down conversion engine ● Auto source format detection (3G/HD/SD) ● DIP switch for video mode and device configurations ● Mini-USB port for configurations and Firmware upgrade ● Region of interest ● Test pattern generator ● Text labels (20 characters)
Input	HDMI x 1
Output	Up/Down Converted HDMI x 1
Supported Video Format	<ul style="list-style-type: none"> ● CEA Format <ul style="list-style-type: none"> ➤ 1080p50/60 ➤ 1080p59.94 ➤ 1080p24/25/30 ➤ 1080p29.97/23.98 ➤ 1080i50/60 ➤ 1080i59.94 ➤ 720p50/60 ➤ 720p59.94 ➤ 625i (PAL) ➤ 525i (NTSC) ● VESA format <ul style="list-style-type: none"> ➤ 640x480@60Hz ➤ 800x600@60Hz ➤ 1024x768@60Hz ➤ 1280x720@60Hz ➤ 1280x1024@60Hz ➤ 1400x1050@60Hz ➤ 1440x900@60Hz ➤ 1600x1200@60Hz ➤ 1920x1080@60Hz
Supported Audio Format	Up to 8 channels, 24bit, 48KHz
Plug & Play	✓
DC In	7.5V ~ 15V